

ARMOURCOAT LIMITED

Material Safety Data Sheet

AQUAWAX

Section 1

Manufactures Name: Armourcoat Limited	Emergency Telephone Number: 0044 1732 460668
Address: Morewood Close, London Road, Sevenoaks, Kent. TN13 2HU United Kingdom	Telephone Number for Information: 0044 1732 460668
	Date Prepared: 20.04.00

Section 2 – Hazard Ingredients / Identity Information

Hazardous Components	OSHA PEL*	ACGIH TLV*	Other Limits Recommended	%
No Hazard Classification according to 88/379/EEC			-	-
Paraffin Wax	2mg m3 / 8hr	6mg m3/8hr	-	-
2-aminoethanol	8mg m3/15 min	15mg m3/15 min	-	-

ARMOURCOAT LIMITED

Material Safety Data Sheet

AQUAWAX

Section 3 – Physical / Chemical Characteristics

Boiling Point	100 C	Specific Gravity (H ₂ O = 1)	1
Vapor Pressure (mmHg.)	As water	Melting Point	N/A
Vapor Density (Air = 1)	0.96 @ 20 C	Evaporation Rate (Butyl Acetate = 1)	-
Solubility in Water	Fully miscible		
Appearance and Odor	White liquid – Bland odour.		

Section 4 – Fire & Explosion Hazard Data

Flash Point Method Used:	Flammable Limits	LEL	UEL
Other tests: ASTM E84-98 (NFPA 255, ANSI/UL 723 / UBC 8-1)	Low Flammable Hazard	-	-
BS 476: Part 6: 1989	FSI = 10.4 SDI = 9.3 Class 0		
Extinguishing Media: Water, Foam, Dry Powder, Water			
Unusual Fire and Explosion Hazards			
Dried wax is combustible.			

ARMOURCOAT LIMITED

Material Safety Data Sheet

AQUAWAX

Section 5 – Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	
Incompatibility (Materials to Avoid)			
None.			
Hazardous Decompositions or Byproducts			
None.			
Hazardous Polymerization	May occur		Conditions to Avoid
	Will not occur	X	

Section 6 – Health Hazard Data

Route (s) of Entry:	Inhalation?	Skin?	Ingestion?
	X	X	X
Health Hazards (Acute and Chronic)			
Eye Contact - Transient stinging. Skin - Irritant and Dermatitis if use repeatedly Ingestion - Irritation of mouth. Ingestion of large quantities may cause vomiting. Inhalation - Irritation			
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
-	-	-	-
Signs and Symptoms of Exposure:			
N/A.			
Medical Conditions Generally Aggravated by Exposure:			

ARMOURCOAT LIMITED

Material Safety Data Sheet

AQUAWAX

Irritation to skin possibly leading to dermatitis.

Emergency and First Aid Measures:

Eye: Irrigate with water immediately. Obtain medical attention if symptoms persist.
Skin: Soap flush as soon as possible. If symptoms persist seek medical attention.
Breathing: Remove from exposure. If irritation develops contact medical help.
Swallow: Wash out with water. Do not induce vomiting.

Section 7 – Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled:

Should not be washed into drains.
Soak up residue with sand.

Waste Disposal Method:

Disposal should be in accordance with current local and national legislation.

Precautions to Be Taken in Handling and Storing:

Avoid contact with skin and eyes during handling – use suitable industrial safety and hygiene practices.

Store in a cool dry place in original packaging – temperature between 5 C and 25 C. Bulk tanks should be externally vented.

Other Precautions: None.

ARMOURCOAT LIMITED

Material Safety Data Sheet

AQUAWAX

Section 8 – Control Measures

Respiratory Protection: None		
Ventilation	Local Exhaust (If spraying)	Special
	Mechanical (General)	Other
Protective Gloves X		Eye Protection X
Other Protective Clothing or Equipment: Suitable Overalls.		
Work / Hygienic Practices: Personal hygiene important, including use of barrier creams.		

Appendix

Material Safety Data Sheet used in compliance with the OSHA's Hazard Communication Standard.

OSHA PEL – Occupational Safety & Health Administration Permissible Exposure Limit.

ACGIH TLV – American Conference of Governmental Industrial Hygienists Tolerable Level Value

NTP – National Toxicology Program

FSI – Flame Spread Index

SDI – Smoke Developed Index

BS – British Standard